# SSR MOTORSPORTS

SSR Motorsports, since 2002 we have been building the products that open up the world of riding.

What sets SSR apart is our focus on bringing cutting edge design, superior engineering, and value for money to the smaller displacement market. We believe that every enthusiast should be able to afford a brand new powersport product from a comprehensive dealer network, with the backing of an expansive distribution center stocked with readily available replacement parts.

Thank you for your interest, whether you are looking for a vehicle for yourself or a vehicle to share the riding experience with your family; whether your interest is ribbons of asphalt or your favorite stretch of dirt road; our knowledgeable and experienced staff is on hand to provide you with the customer service and technical support you need.

# **QUOTABLE QUOTES**

# MOTORCYCLE.COM

- "Needless to say, we're hugely impressed with the SSR Razkull 125. For less than \$2,000 you can have a fun little runabout that looks good, performs well, and does all the tasks you'd want from a small play bike."
- "We were pleasantly surprised by the Benelli TnT300. Killer looks, a sweet exhaust note, a fun chassis, and the right price all are big factors in its favor, making it the one we'd pick of the two." (VS a Honda CB300F)
- "If you've read any of our reviews of SSR or Benelli products in the past, you'll see how impressed we've been already."

# **ULTIMATE** MOTORCYCLING

- "The 2018 Benelli TNT 135 is a rocket."
- "The TNT 300 is a fun machine to ride that doesn't have any real-world limitations."



- "Both the Classic and Cafe are lightweight, inexpensive, and easy to ride machines that offer with plenty of smiles, and isn't that what motorcycles are all about?"

# Gyala Nave

- "Throttling away from a stop, the TNT 600 proves to be a more spirited middleweight than expected, despite its extra heft. Throttle response is neither twitchy nor sluggish but a nice goldilocks of sensitivity."
- "The peppy little single-cylinder motor, good all-day comfort, good cornering performance and great looks great looks combine with that lovely low price tag to make for a genuinely cool little bike that's great fun to ride—and isn't that why we all ride in the first place?" (TNT135)



**BUSINESS CARD** 

All figures based on the latest information at time of publication and subject to change without notice and obligation. Contact your local dealer for specific availability. Obey the law and always wear a dot approved helmet, appropriate eye protection, and proper clothing whenever you ride. Read your owner's manual and inspect your vehicle before riding. Respect the rights of others when you ride, never ride after consuming drugs or alcohol, and never race other vehicles. Vehicle photos and specifications in this brochure reflect models sold in the USA only. Visit www.ssrmotorsports.com for more information. Benelli, the Benelli Logo, and Benelli model names are registered trademarks of Benelli QJ/Benelli Motorcycles USA. SSR Motorsports is the exclusive distributor of Benelli motorcycles and scooters. SSR Motorsports, the SSR logo, and SSR model names are trademarks of SSR Motorsports. © 2019 SSR Motorsports. Printed in the USA.



### SSR MOTORSPORTS

12825 Alondra Blvd. • Norwalk, CA 90650 Ph: (562) 926-2888 Fx: (562) 926-6999 www.ssrmotorsports.com







#### **SPECIFICATIONS**

Inline 2-cylinder, Liquid-cooled. Displacement 300 cc

65 mm x 45.2 mm Bore And Stroke Compression Ratio 37.5 hp @ 11,000 rpm Rated Output Rated Torque 18.9 ft lb @ 9.000 rpm

📟 Benelli

6 Speed

4-valve Per Cylinder, DOHC, EFI

Brake, FR | RR Tire, FR I RR DIMENSION Seat Height

CHASSIS

Ground Clearance Fuel Tank Weight L x W x H

Front Suspension 41 mm. Inverted Spring Preload & Reb. Adj. Shock Rear Suspension 260 mm Dual Disc | 240 mm Disc 120/70-17 | 160/60-17

> 55.51 inches 31.3 inches 6.9 inches 4.2 gallons 408 pounds 83.86" x 31.5" x 44.1"

> > >> NAKED SPORT



# **SPECIFICATIONS**

Inline 4-cylinder, Water-cooled, 4-valve Per Cylinder, DOHC, EFI Displacement

Bore And Stroke Compression Ratio Rated Output Rated Torque

599.6 cc 65 mm x 45.2 mm 11.5:1 67.1 hp @ 11,000 rpm 35.4 ft lb @ 9.000 rpm 6 Speed

Front Suspension Rear Suspension Brake, FR | RR Tire FR I RR

50 mm, Inverted Spring Preload & Reb. Adj. Shock 320 mm Dual Disc | 260 mm Disc 120/70-17 | 180/55-17

Seat Heiaht 31.5 inches Ground Clearance 7.1 inches 3.96 gallons Weight 459 pounds I x W x H 85.03" x 31.5" x 46.5"



Engine Type

> THE NEXT

SMALL

**BIG** 

THING

Single-cylinder, Water-cooled,

249.8 cc Displacement Bore And Stroke 69 mm x 66.8 mm Compression Ratio 10.7:1 18.1 hp @ 6,500 rpm Rated Output 14.75 ft lb @ 6,000 rpm

Transmission V-belt Automatic 📟 Benelli

Front Suspension Rear Suspension Coil Spring Oil Damped 190 mm Dual Disc | 190 mm Disc Brake, FR | RR Tire, FR | RR DIMENSIONS

Wheelbase Seat Height Ground Clearance Fuel Tank Weight

31.75 inches 4.1 inches 2.83 gallons 427 pounds 84.25" x 31.5" x 55.75"

Telescopic Forks

120/70-14 | 140/60-14



## **SPECIFICATIONS**

**Engine Type** 

Single-cylinder, Oil-cooled. 4-valve Per Cylinder, SOHC, EFI Displacement 134.7 cc 54 mm x 58.8 mm Bore And Stroke Compression Ratio

11.3 hp @ 8,500 rpm Rated Output Rated Torque 7.4 ft lb @ 7.000 rpm 5 Speed

📟 Benelli

CHASSIS Front Suspension

Rear Suspension Brake, FR | RR Tire. FR I RR DIMENSION

Seat Height Ground Clearance Fuel Tank Weight LxWxH

41 mm. Inverted Spring Preload & Reb. Adj. Shock 220 mm Disc | 190 mm Disc 120/70-12 | 130/70-12

47.8 inches 30.7 inches 6.3 inches 1.9 gallons 255.7 pounds 68.9" x 29.7" x 40.4"

>> NAKED SPORT



#### **SPECIFICATIONS**

Engine Type Displacement Bore And Stroke

Rated Output

Rated Torque

Starter

Single-cylinder, Air-cooled, 20 mm Carburetor 125 cc 52.4 mm x 55.5 mm Compression Ratio 9.0:1 8.3 hp @ 7,500 rpm 6.9 ft lb @ 4.800 rpm

Flectric / Kick

Hydraulic, Inverted Front Suspension Rear Suspension Brake, FR | RR Tire, FR | RR

Wheelbase Seat Heiaht Ground Clearance Weight

I x W x H

Mono Shock Disc | Disc 120/70-12 | 120/70-12

29.5 inches 6 inches 3.17 gallons 225 pounds 69.7" x 29.8" x 34.8'



FFI 250 cc Displacement

Bore And Stroke 49 mm x 66 mm Compression Ratio 10.0 • 1 Rated Output 18.1 hp @ 8,000 rpm 13.6 ft lb @ 6,000 rpm Rated Torque Transmission 5 Speed

SST

> ADDS

TO YOUR

Rear Suspension Hydraulic Brake, FR | RR Disc | Disc Tire, FR | RR

100/80-17 | 130/90-15 DIMENSION Wheelbase 56.7 inches

Seat Height 31 inches Ground Clearance 8 inches Fuel Tank 3.43 gallons Weight 283 pounds LxWxH 81" x 29.5" x 43"



#### **SPECIFICATIONS**

EFI 250 cc Displacement Bore And Stroke 49 mm x 66 mm Compression Ratio Rated Output

100.1 18.1 hp @ 8,000 rpm Rated Torque Transmission 5 Speed

Rear Suspension Brake, FR | RR Tire, FR | RR

DIMENSION Wheelbase 56.7 inches Seat Height Ground Clearance Fuel Tank Weiaht

31 inches 8 inches 3.43 gallons 283 pounds LxWxH 81" x 29.5" x 43"

Hydraulic

Disc | Disc

100/80-17 | 130/90-15



#### **SPECIFICATIONS**

Displacement Bore And Stroke Compression Ratio Rated Output Rated Torque Transmission

249 cc 72 mm x 61 2 mm 9.4:1 18.1 hp @ 7,000 rpm 10.7 ft lb @ 8.500 rpm 5 Speed

Single-cylinder, Air-cooled.

26 mm Carburetor

Seat Height

Front Suspension

Rear Suspension

Brake, FR | RR

Tire, FR | RR

41 mm Compression Adi., Inverted Standard Coil Spring Shock 250 mm Disc | 240 mm Disc 110/70-17 | 130/70-17

34.5 inches Ground Clearance 7.5 inches 2.6 gallons Weight I x W x H

328 pounds 80" x 30.5" x 43'

